



M300 RTK Release Notes

| | | |
|--------------------------------------|---|----------------------------------|
| Released Date: | 2023.10.30 | |
| Aircraft Firmware: | v07.00.01.00 (for DJI Smart Controller Enterprise) | v58.00.00.09 (for DJI RC Plus) |
| Remote Controller Firmware: | v07.00.01.01 (DJI Smart Controller Enterprise) | v02.02.05.07 (DJI RC Plus) |
| Pilot 2 App: | v7.0.2.5 (built-in DJI Smart Controller Enterprise) | v8.0.0.38 (built-in DJI RC Plus) |
| Intelligent Battery Station: | v07.00.00.05 (BS60) | v07.00.00.07 (BS65) |
| Intelligent Flight Battery: | v01.02.05.44 (BS60) | v09.03.00.45 (TB65) |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) | |
| Zenmuse H20 / H20T: | v07.00.01.05 | |
| Zenmuse H20N: | v07.00.01.05 | |
| Zenmuse P1: | v07.00.01.10 | |
| Zenmuse L1: | v07.00.01.10 | |
| Zenmuse L2: | v01.00.00.01 | |
| Zenmuse Z30: | v01.00.07.10 | |
| Zenmuse XT2: | v01.00.03.50 | |
| Zenmuse XT S: | v01.00.00.09 | |
| DJI X-Port: | v01.03.05.01 | |
| DJI Skyport: | v01.04.00.00 | |
| DJI Skyport V2: | v01.03.05.00 | |
| DJI Assistant 2 (Enterprise Series): | v2.1.11 | |
| Firmware Upgrade Methods: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) | |

What's new

- Added support for Zenmuse L2.

Notes:

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.



M300 RTK Release Notes

- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1, H20, H20T, and H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.



M300 RTK Release Notes

| | | |
|--------------------------------------|---|----------------------------------|
| Released Date: | 2023.09.18 | |
| Aircraft Firmware: | v07.00.01.00 (for DJI Smart Controller Enterprise) | v57.01.00.01 (for DJI RC Plus) |
| Remote Controller Firmware: | v07.00.01.01 (DJI Smart Controller Enterprise) | v02.02.04.45 (DJI RC Plus) |
| Pilot 2 App: | v7.0.2.5 (built-in DJI Smart Controller Enterprise) | v7.1.0.32 (built-in DJI RC Plus) |
| Intelligent Battery Station: | v07.00.00.04 (BS60) | v07.00.00.05 (BS65) |
| Intelligent Flight Battery: | v01.02.05.44 (BS60) | v09.03.00.44 (TB65) |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) | |
| Zenmuse H20 / H20T: | v07.00.01.05 | |
| Zenmuse H20N: | v07.00.01.05 | |
| Zenmuse P1: | v07.00.01.10 | |
| Zenmuse L1: | v07.00.01.10 | |
| Zenmuse Z30: | v01.00.07.10 | |
| Zenmuse XT2: | v01.00.03.50 | |
| Zenmuse XT S: | v01.00.00.09 | |
| DJI X-Port: | v01.03.05.01 | |
| DJI Skyport: | v01.04.00.00 | |
| DJI Skyport V2: | v01.03.05.00 | |
| DJI Assistant 2 (Enterprise Series): | v2.1.10 | |
| Firmware Upgrade Methods: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) | |

What's new

- Ortho Collection supports the customization of the gimbal angle.
- Added the function of Find My Drone in Flight Controller Settings. In scenarios such as aircraft emergency landing or flyaway, information such as position display and coordinate sharing help users to find the aircraft.
- Added ability to view the downloaded photos and videos in Album when the aircraft is disconnected.



M300 RTK Release Notes

- Added support to save multiple sets of configurations for custom network RTK.
- Added support to search location by texts, GEO zone alerts, and scan code to obtain target point locations in Map for DJI Pilot 2.
- Added ability to import unlocking licenses offline.
- Optimized UI for Flight Route Library.
- Ortho Collection supports selecting start point for flight routes.

Notes:

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1, H20, H20T, and H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.



M300 RTK Release Notes

| | | |
|--------------------------------------|---|---------------------------------|
| Released Date: | 2023.07.18 | |
| Aircraft Firmware: | v07.00.01.00 (for DJI Smart Controller Enterprise) | v57.00.01.00 (for DJI RC Plus) |
| Remote Controller Firmware: | v07.00.01.01 (DJI Smart Controller Enterprise) | v01.02.04.45 (DJI RC Plus) |
| Pilot 2 App: | v7.0.2.5 (built-in DJI Smart Controller Enterprise) | v7.0.3.9 (built-in DJI RC Plus) |
| Intelligent Battery Station: | v07.00.00.01 (BS60) | v07.00.00.01 (BS65) |
| Intelligent Flight Battery: | v01.02.05.44 (BS60) | v09.03.00.39 (TB65) |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) | |
| Zenmuse H20 / H20T: | v07.00.01.05 | |
| Zenmuse H20N: | v07.00.01.05 | |
| Zenmuse P1: | v07.00.01.10 | |
| Zenmuse L1: | v07.00.01.10 | |
| Zenmuse Z30: | v01.00.07.10 | |
| Zenmuse XT2: | v01.00.03.50 | |
| Zenmuse XT S: | v01.00.00.09 | |
| DJI X-Port: | v01.03.05.01 | |
| DJI Skyport: | v01.04.00.00 | |
| DJI Skyport V2: | v01.03.05.00 | |
| DJI Assistant 2 (Enterprise Series): | v2.1.10 | |
| Firmware Upgrade Methods: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) | |

What's new

- Improved DJI Pilot 2 app stability.

Notes:

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.



M300 RTK Release Notes

- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1, H20, H20T, and H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.



M300 RTK Release Notes

| | | |
|--------------------------------------|---|---------------------------------|
| Released Date: | 2023.06.01 | |
| Aircraft Firmware: | v07.00.01.00 (for DJI Smart Controller Enterprise) | v57.00.01.00 (for DJI RC Plus) |
| Remote Controller Firmware: | v07.00.01.01 (DJI Smart Controller Enterprise) | v01.02.04.43 (DJI RC Plus) |
| Pilot 2 App: | v7.0.2.5 (built-in DJI Smart Controller Enterprise) | v7.0.2.3 (built-in DJI RC Plus) |
| Intelligent Battery Station: | v07.00.00.01 (BS60) | v07.00.00.01 (BS65) |
| Intelligent Flight Battery: | v01.02.05.44 (BS60) | v09.03.00.39 (TB65) |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) | |
| Zenmuse H20 / H20T: | v07.00.01.05 | |
| Zenmuse H20N: | v07.00.01.05 | |
| Zenmuse P1: | v07.00.01.10 | |
| Zenmuse L1: | v07.00.01.10 | |
| Zenmuse Z30: | v01.00.07.10 | |
| Zenmuse XT2: | v01.00.03.50 | |
| Zenmuse XT S: | v01.00.00.09 | |
| DJI X-Port: | v01.03.05.01 | |
| DJI Skyport: | v01.04.00.00 | |
| DJI Skyport V2: | v01.03.05.00 | |
| DJI Assistant 2 (Enterprise Series): | v2.1.9 | |
| Firmware Upgrade Methods: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) | |

What's new

- Added the remaining purchase service information for DJI FlightHub 2 in DJI Pilot 2.
- Optimized some of the DJI Pilot 2 information such as prompts.

Notes:



M300 RTK Release Notes

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1, H20, H20T, and H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.



M300 RTK Release Notes

| | | |
|--------------------------------------|---|---------------------------------|
| Released Date: | 2023.05.18 | |
| Aircraft Firmware: | v07.00.01.00 (for DJI Smart Controller Enterprise) | v57.00.01.00 (for DJI RC Plus) |
| Remote Controller Firmware: | v07.00.01.00 (DJI Smart Controller Enterprise) | v01.02.04.40 (DJI RC Plus) |
| Pilot 2 App: | v7.0.1.1 (built-in DJI Smart Controller Enterprise) | v7.0.1.0 (built-in DJI RC Plus) |
| Intelligent Battery Station: | v07.00.00.01 (BS60) | v07.00.00.01 (BS65) |
| Intelligent Flight Battery: | v01.02.05.44 (BS60) | v09.03.00.39 (TB65) |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) | |
| Zenmuse H20 / H20T: | v07.00.01.05 | |
| Zenmuse H20N: | v07.00.01.05 | |
| Zenmuse P1: | v07.00.01.10 | |
| Zenmuse L1: | v07.00.01.10 | |
| Zenmuse Z30: | v01.00.07.10 | |
| Zenmuse XT2: | v01.00.03.50 | |
| Zenmuse XT S: | v01.00.00.09 | |
| DJI X-Port: | v01.03.05.01 | |
| DJI Skyport: | v01.04.00.00 | |
| DJI Skyport V2: | v01.03.05.00 | |
| DJI Assistant 2 (Enterprise Series): | v2.1.9 | |
| Firmware Upgrade Methods: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) | |

What's new

New Product Support

- Added support for the aircraft to use with DJI RC Plus remote controller.
- Added support for the aircraft to use with the TB65 Intelligent Flight Battery.
- Added support for the BS60 Intelligent Battery Station to use with the TB65 Intelligent Flight Battery.
- Added support for DJI Smart Controller Enterprise to use with the BS65 Intelligent Battery Station, such as updating firmware and exporting Log.



M300 RTK Release Notes

* Visit <https://enterprise.dji.com/matrice-300/downloads>, download and read the Compatible Firmware Update Guide for M300 RTK and M350 RTK and the M350 RTK and M300 RTK Accessory Compatibility List to learn the compatibility between the devices and how to update them to a compatible firmware version.

Optimized Experiences:

- Increased the aircraft wind speed warning threshold from 6 m/s to 10 m/s.

Fixed Issues:

- Fixed an issue where after canceling the distribution of annotation information on the DJI FlightHub 2 webpage, the app cannot show the corresponding annotation information when redistributing.
- Fixed an issue where the options in the photo/video storage settings in the camera menu settings are empty when only selecting the current photo/video in the media storage settings.

Notes:

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1, H20, H20T, and H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2023.03.09 |
| Aircraft Firmware: | v06.01.01.00 |
| Remote Controller Firmware: | v06.01.01.00 |
| Pilot 2 App Android: | v6.1.2.3 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.03 |
| Intelligent Flight Battery: | v01.02.05.44 |
| Zenmuse H20 / H20T: | v04.01.03.00 |
| Zenmuse H20N: | v05.01.01.00 |
| Zenmuse P1: | v04.00.02.05 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.7 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App |
| | Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App |
| | D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Methods: | The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware |
| | Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

- Updated to use GPS+Galileo+BeiDou as the GNSS of the aircraft, which can increase the availability and search speed of satellites in the obstructing environment.
- Added countdown prompt for IMU Calibration in Manual Flight when using the Zenmuse L1.
- Added Support for Terrain Follow in Smart Oblique, Oblique Photography, and Linear Flight tasks.
- Added ability to execute flight tasks during flight for fast and efficient execution of flight tasks at the



M300 RTK Release Notes

current location. Tap the flight route icon to create or select a flight task on the camera or map view of the DJI Pilot 2 app.

- Added ability to set Safe Takeoff Altitude for flight tasks to improve flight safety. This parameter setting is only valid when the aircraft executes a flight task before takeoff. If the aircraft starts a flight task during flight, the safe takeoff altitude will not take effect.
- Added ability to create Mapping or Oblique tasks by selecting an area in the map view. Convenient to generate a flight route after synchronizing the mapping area planned on DJI FlightHub 2 to the DJI Pilot 2 app.
- Added ability to import MBTiles format maps downloaded from Maptiler. The map layer can be customized in the DJI Pilot 2 app.
- Added ability to export logs by different modules in the DJI Pilot 2 app.
- Added encryption for Network Security Mode in the DJI Pilot 2 app. After setting a password, users can only change the Network Security Mode or adjust the function settings after entering the password.
- Optimized firmware update prompt in the DJI Pilot 2 app.
- Fixed an occasional issue where the aircraft accidentally hovered during Waypoint Mission flight tasks.
- Fixed issue where Night Scene mode cannot be used properly when using the Zenmuse H20N attached to the 2nd gimbal port of the aircraft.

Notes:

- If there is a need to downgrade to an earlier firmware version after updating to the latest firmware version, make sure to back up the flight route files in advance to prevent the flight route files from being lost due to the incompatibility of the app database version.
- Once the firmware version has been updated in the United States, it cannot be downgraded to v04.01.00.00 or lower to meet the US policy requirements.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1 or H20 / H20T/H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2022.12.02 |
| Aircraft Firmware: | v05.01.01.00 |
| Remote Controller Firmware: | v05.01.02.00 |
| Pilot 2 App Android: | v5.1.1.7 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.03 |
| Intelligent Flight Battery: | v01.02.05.44 |
| Zenmuse H20 / H20T: | v04.01.03.00 |
| Zenmuse H20N: | v05.01.01.00 |
| Zenmuse P1: | v04.00.02.05 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.6 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App |
| | Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App |
| | D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Methods: | The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware |
| | Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

- Fixed issue where importing the KMZ file failed.
 - Fixed issue where the aircraft flew to the start point from the break point when resuming flight in Terrain Follow mode.
 - Fixed issue where the maximum speed limit is too low when using Zenmuse P1 to plan the flight route task.*
- * If the flight route speed of the KMZ file for Zenmuse P1 has been limited due to the remote controller**



M300 RTK Release Notes

firmware update (v05.01.01.00), edit the flight route speed of the KMZ file after updating to this firmware version and save the file.

Notes:

- Once the firmware version has been updated in the United States, it cannot be downgraded to v04.01.00.00 or lower to meet the US policy requirements.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1 or H20 / H20T/H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2022.11.22 |
| Aircraft Firmware: | v05.01.01.00 |
| Remote Controller Firmware: | v05.01.01.00 |
| Pilot 2 App Android: | v5.1.1.5 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.03 |
| Intelligent Flight Battery: | v01.02.05.44 |
| Zenmuse H20 / H20T: | v04.01.03.00 |
| Zenmuse H20N: | v05.01.01.00 |
| Zenmuse P1: | v04.00.02.05 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.4 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App |
| | Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App |
| | D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Methods: | The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware |
| | Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

- Added support for FAA's Remote ID requirements in the United States.
- Added support for DJI Pilot 2 to download online geoid files.
- Added support for importing and exporting MapTiler offline maps.
- Added support for DJI Pilot 2 message notifications.
- Optimized support for Zenmuse XT S, XT 2 and Z30.



M300 RTK Release Notes

- Optimized support for multiple PSDK payloads.
- Fixed issue: When using the dual remote controller mode, Discreet Mode could not be disabled on the aircraft with one of the remote controllers.
- Fixed issue: When the custom camera parameters failed to be applied in Mission Flight at the first time of use.
- Fixed issue: When the remote controller froze after reinserting the HDMI cable with the app running in the background.
- When Aircraft Yaw is set to Control By RC and the yaw angle is adjusted when the mission is paused, the aircraft continues to fly at the adjusted angle after resuming the mission.

Notes:

- Once the firmware version has been updated in the United States, it cannot be downgraded to v04.01.00.00 or lower to meet the US policy requirements.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, L1, P1 or H20 / H20T/H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2022.08.10 |
| Aircraft Firmware: | v04.01.00.00 |
| Remote Controller Firmware: | v04.01.01.01 |
| Pilot 2 App Android: | v4.1.1.14 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.03 |
| Intelligent Flight Battery: | v01.02.05.44 |
| Zenmuse H20 / H20T: | v04.00.00.10 |
| Zenmuse H20N: | v04.01.00.00 |
| Zenmuse P1: | v03.00.01.04 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.3 |
| Firmware Upgrade Methods: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

- Fixed issue where app crashes when displaying ADS-B information on map.
- Fixed issue where recording could not be uploaded when broadcasting with speaker.

Notes:

- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.



M300 RTK Release Notes

- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, P1 or H20 / H20T/H20N.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2022.07.21 |
| Aircraft Firmware: | v04.01.00.00 |
| Remote Controller Firmware: | v04.01.00.00 |
| Pilot 2 App Android: | v4.1.1.11 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.03 |
| Intelligent Flight Battery: | v01.02.05.44 |
| Zenmuse H20 / H20T: | v04.00.00.10 |
| Zenmuse H20N: | v04.01.00.00 |
| Zenmuse P1: | v03.00.01.04 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.3 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App |
| | Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App |
| | D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Methods: | The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware |
| | Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

- Added support for saving Maintain Positioning Accuracy setting after the aircraft is powered off.
- Updated Mapbox to MapTiler. A maximum area of 50 square kilometers of offline map can be downloaded at one time.
- Added support for setting Zenmuse P1 image styles, including sharpness, contrast, and saturation.
- Optimized user experience of AI Spot-Check with Zenmuse H20 and H20T, including downloading photos



M300 RTK Release Notes

from aircraft and saving AI Spot-Check task during flight.

- Fixed occasional issue where aircraft flew off route when resuming task at coordinated turns.
- Fixed issue where aircraft flew in circles when arriving at waypoint after start and end points of Live Mission Recording task were reversed.
- Fixed issue where Side Overlap (LiDAR) and Scanning Mode settings could not be saved when creating LiDAR mapping tasks with Zenmuse L1.
- Fixed display issue where flight records were missing.

Notes:

- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2022.06.20 |
| Aircraft Firmware: | v04.00.03.00 |
| Remote Controller Firmware: | v04.00.03.00 |
| Pilot 2 App Android: | v4.0.1.21 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.03 |
| Intelligent Flight Battery: | v01.02.05.44 |
| Zenmuse H20 / H20T: | v04.00.00.10 |
| Zenmuse H20N: | v04.00.02.00 |
| Zenmuse P1: | v03.00.01.04 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.3 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App |
| | Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App |
| | D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Methods: | The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware |
| | Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

- Added support for Remote ID in Japan.
- Optimized imported KML files. After importing KML files when using Waypoint mission, users can select the flight route altitude from Relative to Takeoff Point (ALT), Ellipsoidal Height (WGS84), and ASL (EGM96).
- Fixed an occasional issue: where the Zenmuse L1 stopped point cloud recording at the turn of a concave mapping area.



M300 RTK Release Notes

Notes:

- If the point cloud recording stops when executing a flight route using an existing KMZ file, update the firmware to the latest version, and re-edit and save the route parameters (such as speed) of the KMZ file. Once complete, the point cloud recording and KMZ file will resume to normal.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2022.05.21 |
| Aircraft Firmware: | v04.00.02.00 |
| Remote Controller Firmware: | v04.00.02.00 |
| Pilot 2 App Android: | v4.0.1.16 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.03 |
| Intelligent Flight Battery: | v01.02.05.44 |
| Zenmuse H20 / H20T: | v04.00.00.10 |
| Zenmuse H20N: | v04.00.02.00 |
| Zenmuse P1: | v03.00.01.04 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.3 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App |
| | Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App |
| | D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Methods: | The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware |
| | Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

- Fixed an occasional issue: where the Intelligent Flight Battery required maintenance and could not be used for flight after updating the firmware to v01.02.05.43.
- Fixed an occasional issue: where the Mission flight files stored in the remote controller failed to display in the flight route library after updating the firmware to v04.00.01.10.
- Fixed issue: where the app crashed when tapping the PSDK shortcut button in the video transmission view.



M300 RTK Release Notes

Notes:

- For a battery with an out-of-date firmware version (and that requires maintenance), make sure the battery level is lower than 90% when updating the firmware. After the firmware update is complete, fully charge the battery and remove it from the battery station. Let the battery sit for two hours before use.
- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.
- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2022.05.11 |
| Aircraft Firmware: | v04.00.01.11 |
| Remote Controller Firmware: | v04.00.01.10 |
| Pilot 2 App Android: | v4.0.1.14 |
| D-RTK 2 Mobile Station for Matrice: | v03.01.00.00 (D-RTK 2 Mobile Station: v03.01.00.00) |
| Intelligent Battery Station: | v04.00.01.02 |
| Intelligent Flight Battery: | v01.02.05.43 |
| Zenmuse H20 / H20T: | v04.00.00.10 |
| Zenmuse H20N: | V04.00.02.00 |
| Zenmuse P1: | v03.00.01.04 |
| Zenmuse L1: | v04.00.01.06 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.3 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App |
| | Zenmuse H20 / H20T: micro SD card / DJI Assistant 2 / App |
| | D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Methods: | The built-in DJI Pilot 2 app: will be updated with the Remote Controller firmware |
| | Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot 2 app.) |

What's new

New Product Support

- Added support for DJI Pilot 2 app, and improved flight safety and task efficiency:
 - (1) Upgraded home screen, and added support for viewing GEO Zone map, album, and device health status, managing unlocking licenses, cloud services, and flight route tasks.
 - (2) Upgraded camera view, and added support for quick control of aircraft and camera and a clearer display

M300 RTK Release Notes

of task information and flight status.

- (3) Adjusted PinPoint size according to the distance between PinPoint and aircraft, and added support for displaying icon indicating Home point and PinPoint positions.
 - (4) Made sure warning messages are displayed accurately and timely, and warning history can be checked quickly.
 - (5) Added support for managing PinPoints, adding, deleting, selecting, and viewing PinPoints using 5D button, and adding lines and areas in map view.
- Added support for DJI FlightHub 2:
 - (1) Added support for cloud livestreams with Zenmuse H20 series.
 - (2) Added support for displaying points, lines, and areas in DJI Pilot 2 and DJI FlightHub 2 at the same time.
 - (3) Added support for real-time media files upload from DJI Pilot 2, viewing photos and panoramas, and managing media files in DJI FlightHub 2.
 - (4) Added support for visible light and infrared cloud mapping with Zenmuse H20 series, and checking mapping data in both DJI Pilot 2 and DJI FlightHub 2.
 - (5) Added support to create cloud flight routes and manage routes in both DJI Pilot 2 and DJI FlightHub 2.
 - Added support for DJI Zenmuse H20N.

Optimized Experiences

- Added support to give priority to charge top and bottom paired batteries in the battery station.
- Added support to zoom camera by scrolling the right dial while pressing the Confirm button.
- Added support for H20 series cameras with a minimum 1.3x zoom.
- Added support for saving Live Mission Recording data during flight (Note: If AI Spot-Check is enabled, photos still need to be downloaded after landing).
- Flight tasks can be paused and resumed in camera view during flight.
- Added support to customize third-party camera parameters.
- Photos and videos are named according to waypoint name.
- Optimized flight route descriptions.

Fixed Issues

- Where occasionally LED 1 and 2 then LED 3 and 4 alternately blinked on the flight battery (v01.02.05.40) and failed to charge. The TB60 battery status indicator on the battery station blinked yellow to alert the

M300 RTK Release Notes

user the batteries were not charging.

- Where the default warning distance was smaller than the braking distance in the obstacle sensing setting for the aircraft.
- When the aircraft is powered on and the radar module is removed, the aircraft will send false alerts after takeoff.
- Where one flight route was occasionally missed when using Mission flight.

Notes:

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later.**
- The aircraft cannot revert to firmware version v01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- DJI Pilot app must be updated to v3.0.1.4 or later to use Offline Update.



M300 RTK Release Notes

| | |
|--------------------------------------|--|
| Released Date: | 2022.03.14 |
| Aircraft Firmware: | v03.01.00.14 |
| Remote Controller Firmware: | v03.01.00.10 |
| Pilot App Android | v3.1.1.3 (M300) |
| D-RTK 2 Mobile Station for Matrice: | v03.00.00.16 (D-RTK 2 Mobile Station: v02.02.0505) |
| Intelligent Battery Station: | v03.00.01.01 |
| Intelligent Flight Battery: | v01.02.05.40 |
| Zenmuse H20 / H20T: | v03.00.01.02 |
| Zenmuse P1 | v03.00.01.04 |
| Zenmuse L1 | v03.00.02.00 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.2 |
| Firmware Upgrade Method: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

- Updated the default period for triggering self-discharge to two days, reducing the storage time at high battery level to prolong battery life.
- Added a strategy where aircraft is prevented from flying when the battery temperature is lower than 10°C, and increased the self-heating cut-off temperature of the battery, so that the battery can work at room temperature (discharge performance is better at room temperature than low temperature), thereby improving flight safety.
- Fixed an occasional issue: where the battery could not be charged due to voltage sampling error or failure to update.

Notes

<http://www.dji.com/matrice-300>

Copyright © 2020 DJI All Rights Reserved.



M300 RTK Release Notes

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise, the aircraft will work abnormally.**
- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V2.2.1.7 or later.
- DJI Pilot app must be updated to v.3.0.1.4 to use Offline Update.



M300 RTK Release Notes

| | |
|--------------------------------------|--|
| Released Date: | 2021.11.30 |
| Aircraft Firmware: | v03.00.01.01 |
| Remote Controller Firmware: | v03.01.00.00 |
| Pilot App Android | V3.0.1.9(M300) |
| D-RTK 2 Mobile Station for Matrice: | v03.00.00.16 (D-RTK 2 Mobile Station: v02.02.0505) |
| Intelligent Battery Station: | v03.00.01.01 |
| Intelligent Flight Battery: | v01.02.05.31 |
| Zenmuse H20 / H20T: | v03.00.01.02 |
| Zenmuse P1 | v03.00.01.04 |
| Zenmuse L1 | v03.00.02.00 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.2 |
| Firmware Upgrade Method: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

- Fixed issue: customized RTK network connection failed in some countries.
- Fixed issue: Pin Point was displayed at bottom of remote controller screen when takeoff altitude was negative.
- Fixed issue: relative height was incorrectly displayed by default instead of altitude when aircraft entered Live Mission Recording in RTK mode.
- Fixed issue: abnormal metadata appeared in live view.

Notes



M300 RTK Release Notes

- Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise, the aircraft will work abnormally.
- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V2.2.1.7 or later.
- DJI Pilot app must be updated to v.3.0.1.4 to use Offline Update.



M300 RTK Release Notes

| | |
|--------------------------------------|--|
| Released Date: | 2021.10.13 |
| Aircraft Firmware: | v03.00.01.01 |
| Remote Controller Firmware: | v03.00.01.02 |
| Pilot App Android | V3.0.1.4(M300) |
| D-RTK 2 Mobile Station for Matrice: | v03.00.00.16 (D-RTK 2 Mobile Station: v02.02.0505) |
| Intelligent Battery Station: | v03.00.01.01 |
| Intelligent Flight Battery: | v01.02.05.31 |
| Zenmuse H20 / H20T: | v03.00.01.02 |
| Zenmuse P1 | v03.00.01.03 |
| Zenmuse L1 | v03.00.01.00 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.1 |
| Firmware Upgrade Method: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

- Added Offline Update. Offline firmware package can be downloaded from DJI official website to external storage device such as SD card or U disk. Use DJI Pilot to select firmware of remote controller, aircraft, payload, or battery station from the external storage device to update.
- Added one-tap panorama shots when used with Zenmuse H20 series gimbal and camera.
- Added Data and Privacy settings in DJI Pilot, including Network Security Mode, Security Code, and Clear DJI Device Data. When using Security Code, users can download DJI Decrypt Tool PC from DJI official website to decrypt encrypted SD card for access on Windows system.
- For Flight Controller Settings in DJI Pilot:
 - A. Introduced Coordinated Turn.



M300 RTK Release Notes

- B. The satellite positioning system can be switched between BeiDou and GPS+GLONASS.
- C. Increased height limit to 1500 m, except for when within 50 km of airport. Increase height limit only valid until aircraft powered on. Height limit returns to 500 m when aircraft restarted.
- For RTK Settings in DJI Pilot:
 - A. RTK Positioning can be enabled and disabled during flight. Select RTK Service Type first.
 - B. Added Maintain Positioning Accuracy mode.
- For HMS in DJI Pilot:
 - A. Added DJI Care Enterprise.
 - B. Added DJI Maintenance Program.
 - C. Error Records available for battery and battery station (required to connect battery station to remote controller via USB-C cable).
 - D. Manage Logs available for battery and battery station (required to connect battery station to remote controller via USB-C cable).
- Adjusted DJI AirSense warning strategy to reduce the probability of false alarms according to UAV flight characteristics. Optimized DJI Airsense alert interaction in DJI Pilot and added AR projection display in live view to improve flight safety.
- Optimized Mission Flight:
 - A. The aircraft will decelerate when pulling down pitch stick of remote controller during Mission Flight.
 - B. Remote controller cannot control aircraft yaw when Aircraft Yaw is set to Along Route in flight route settings.
 - C. The Mission Flight can be paused by pressing the Pause button on the remote controller or via DJI Pilot app, and can only be resumed via DJI Pilot app.
 - D. Added acceleration and deceleration calibration flight for L1 payload (except for Linear Flight Mission).
- Optimized Return-to-Home (RTH):
 - A. Added tip in DJI Pilot to remind users to exit Auto-RTH and manually control aircraft to return to home point when encountering obstacles during RTH.
 - B. Added ability to exit Auto-RTH by moving remote controller control stick in opposite direction of flight.
- Optimized PinPoint during Manual Flight:
 - A. Allowed users to edit and manage multiple Pin Points.
 - B. Allowed users to set a Pin Point as home point.
- Optimized frequency selection of video transmission to improve anti-interference performance. Added tips in DJI Pilot when aircraft and remote controller experience interference.
- Optimized PSDK and OSDK interaction for improved user experience.
- Improved shot accuracy of mapping camera.
- Fixed some minor bugs.



M300 RTK Release Notes

Notes

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise, the aircraft will work abnormally.**
- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V2.2.1.7 or later.
- DJI Pilot app must be updated to v.3.0.1.4 to use Offline Update.

M300 RTK Release Notes

| | |
|--------------------------------------|---|
| Released Date: | 2021.05.10 |
| Aircraft Firmware: | v02.04.01.02 |
| Remote Controller Firmware: | v02.04.01.03 |
| Pilot App Android | v2.4.1.7 (M300) |
| D-RTK 2 Mobile Station for Matrice: | v03.00.00.16 (D-RTK 2 Mobile Station: v02.02.0505) |
| Intelligent Battery Station: | v02.04.01.01 |
| Intelligent Flight Battery: | v01.02.05.31 |
| Zenmuse H20 / H20T: | v02.04.01.01 |
| Zenmuse P1 | v02.04.01.02 |
| Zenmuse L1 | v02.04.01.00 or later |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 (Enterprise Series): | v2.1.0 |
| Firmware Upgrade Method: | <p>Aircraft / Remote Controller: DJI Assistant 2 / App</p> <p>Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App</p> <p>D-RTK 2 Mobile Station: DJI Assistant 2</p> <p>The built-in DJI Pilot app: will be updated with the Remote Controller firmware</p> <p>Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.)</p> |

What's new

- Added support for DJI Zenmuse L1 gimbal and camera, offering users a complete integrated solution that includes a Livox LiDAR module and a 1-inch CMOS camera sensor.
- Added Altitude Mode to mission flight when using a PSDK 102S camera.
- Optimized calculation method to estimate the amount of time to take photos and also the number of photos left to take, providing users with greater accuracy.
- Fixed issue: the mission could not be uploaded if the altitude was above 5,000 m during a mission flight.
- Fixed issue: when using the Zenmuse H20T, Sun Burn Protection was not disabled even if the Sun Burn Protection Disabled button has been pressed in the app.



M300 RTK Release Notes

Notes:

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise, the aircraft will work abnormally.**
- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the ZenmuseZ30, XT S, XT2, P1 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V2.2.1.7 or later.



M300 RTK Release Notes

| | |
|-------------------------------------|--|
| Released Date: | 2021.03.19 |
| Aircraft Firmware: | v02.02.03.01 |
| Remote Controller Firmware: | v02.02.01.02 |
| Pilot App Android | v2.2.1.7 |
| D-RTK 2 Mobile Station for Matrice: | v03.00.00.16 (D-RTK 2 Mobile Station: v02.02.0505) |
| Intelligent Battery Station: | v01.05.06.07 |
| Intelligent Flight Battery: | v01.02.05.30 |
| Zenmuse H20 / H20T: | v02.02.01.00 |
| Zenmuse P1 | v02.02.01.00 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 For Matrice: | v2.0.13 |
| Firmware Upgrade Method: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

- Fixed rare issue: error occurred in Mission Flight. It is highly recommended to update firmware to latest version.
- Fixed occasional issue: the aircraft would brake at a distance of 5 meters from the obstacle in the upward direction even if the braking distance was set to more than 5 meters.

Notes:

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise, the aircraft will work abnormally.**



M300 RTK Release Notes

- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V2.2.1.7 or later.



M300 RTK Release Notes

| | |
|-------------------------------------|--|
| Released Date: | 2021.02.22 |
| Aircraft Firmware: | v02.02.02.01 |
| Remote Controller Firmware: | v02.02.01.02 |
| Pilot App Android | v2.2.1.7 |
| D-RTK 2 Mobile Station for Matrice: | v03.00.00.16 (D-RTK 2 Mobile Station: v02.02.0505) |
| Intelligent Battery Station: | v01.05.06.07 |
| Intelligent Flight Battery: | v01.02.05.30 |
| Zenmuse H20 / H20T: | v02.02.01.00 |
| Zenmuse P1 | v02.02.01.00 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 For Matrice: | v2.0.13 |
| Firmware Upgrade Method: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

- Fixed issue: the absolute altitude value was incorrect in the metadata of photos taken by a PSDK camera such as PSDK 102S.

Notes:

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise, the aircraft will work abnormally.**
- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used)



M300 RTK Release Notes

are updated to the latest firmware version.

- Download the latest firmware from official website to microSD card to update the Zenmuse Z30, XT S, XT2, P1 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V2.2.1.7 or later.



M300 RTK Release Notes

| | |
|-------------------------------------|--|
| Released Date: | 2021.02.01 |
| Aircraft Firmware: | v02.02.01.02 |
| Remote Controller Firmware: | v02.02.01.02 |
| Pilot App Android | v2.2.1.7 |
| D-RTK 2 Mobile Station for Matrice: | v03.00.00.16 (D-RTK 2 Mobile Station: v02.02.0505) |
| Intelligent Battery Station: | v01.05.06.07 |
| Intelligent Flight Battery: | v01.02.05.30 |
| Zenmuse H20 / H20T: | v02.02.01.00 |
| Zenmuse P1 | v02.02.01.00 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Skyport: | v01.04.00.00 |
| DJI Skyport V2: | v01.03.02.00 |
| DJI Assistant 2 For Matrice: | v2.0.13 |
| Firmware Upgrade Method: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

- Added support for DJI Zenmuse P1 gimbal and camera.
- Added support for CSM Radar, which can be used with M300 RTK for obstacle avoidance.
- Optimized display in both camera and FPV view. Updated absolute altitude display (ASL) of the aircraft and RNG points from the ellipsoid height to the altitude (using EGM96 model).
- Optimized Mission Flight:
 - (1) Added Terrain Awareness Mode to Mapping Mission. Import a DSM file with ground height information included in order to enter the mode.
 - (2) Disabled record and focus/shutter buttons on remote controller during Mapping, Oblique, and Linear Flight Missions to avoid accidentally interrupting operations.



M300 RTK Release Notes

- (3) Added H20 infrared camera and PSDK 102S to camera list when planning flight missions.
- (4) Added description when flight mission is paused.
- (5) Optimized gimbal control mechanism to ensure successful control.
- (6) Fixed issue: not all photos taken during a mission flight were saved.
- (7) Fixed issue: the gimbal yaw rotated abnormally during Waypoint, Mapping, Oblique, and Linear Flight Missions.
- (8) Fixed occasional issue: the last Waypoint could not be executed.
- (9) Fixed occasional issue: unable to automatically exit the Mission Flight once completed.
- Optimized Return-to-Home (RTH):
 - (1) Updated default RTH altitude to 100 m (328 ft).
 - (2) Updated max RTH flight speed to 15 m/s.
 - (3) Updated RTH logic.
 - A. Vision system enabled: If RTH is triggered within 50 m (164 ft) from the home point, the aircraft will return to the home point at the current altitude. If RTH is triggered farther than 50 m (164 ft) from the home point, the aircraft will return to the home point at the RTH altitude. Once the aircraft is higher than the RTH altitude, it will return to the home point at the current altitude.
 - B. Vision system disabled: the aircraft will return to the home point at the RTH altitude. Once the aircraft is higher than the RTH altitude, it will return to the home point at the current altitude.
- Added restriction so that takeoff is disabled when the remote controller battery level is below 10%.
- Added sound recording when the remote controller is recording the screen.
- Added support for live streaming (GB28181 standard).
- Fixed issue: the D-RTK 2 Mobile Station cannot be found in some areas
- Fixed occasional issue: the incorrect date was displayed on the remote controller.
- Fixed issue: there was no feedback sound when adjusting the media volume on the remote controller.
- Fixed issue: playback speed was slow when connected to DJI Pilot on another mobile device.
- Fixed issue: unable to resume an interrupted flight route when using the Mapbox service.
- Fixed issue: the camera mistakenly zooms in or out when using the gimbal control stick of the remote controller to control the pitch in Advanced Dual Operator Mode.
- Fixed occasional issue: unable to set Night mode and 4K resolution for the Zoom camera of H20.
- Fixed occasional issue: unable to use a battery because it could not be authenticated.
- Fixed occasional issue: unable to reconnect once the Custom Network RTK disconnected.

Notes:

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise,**



M300 RTK Release Notes

the aircraft will work abnormally.

- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the ZenmuseZ30, XT S, XT2 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V2.2.1.7 or later.



M300 RTK Release Notes

| | |
|------------------------------|--|
| Released Date: | 2021.01.01 |
| Aircraft Firmware: | v01.00.02.14 |
| Remote Controller Firmware: | v01.00.02.14 |
| Pilot App Android | v1.9.1R |
| D-RTK 2 Mobile Station: | v03.00.00.13 |
| Intelligent Battery Station: | v01.05.06.06 |
| Intelligent Flight Battery: | v01.02.05.28 |
| Zenmuse H20 / H20T: | v01.00.02.11 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Assistant 2 For Matrice: | v2.0.13 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Method: | The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

Remote Controller Firmware

- Fixed issue: DJI Pilot stopped running when using M300 RTK in Mainland China.

Notes:

- **Users who use Custom Network RTK must update the aircraft firmware to v01.00.02.14 or later. Otherwise, the aircraft will work abnormally.**
- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the ZenmuseZ30, XT S, XT2 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V1.9.1R or later.



M300 RTK Release Notes

| | |
|------------------------------|--|
| Released Date: | 2020.11.26 |
| Aircraft Firmware: | v01.00.02.14 |
| Remote Controller Firmware: | v01.00.02.13 |
| Pilot App Android | v1.9.0R |
| D-RTK 2 Mobile Station: | v03.00.00.13 |
| Intelligent Battery Station: | v01.05.06.06 |
| Intelligent Flight Battery: | v01.02.05.28 |
| Zenmuse H20 / H20T: | v01.00.02.11 |
| Zenmuse Z30: | v01.00.07.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.03.02.00 |
| DJI Assistant 2 For Matrice: | v2.0.13 |
| Firmware Upgrade Method: | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

Aircraft Firmware

- Improved GNSS stability when using the Custom Network RTK.

Notes:

- **Users who use Custom Network RTK MUST update to this firmware version. Otherwise, the aircraft will work abnormally.**
- The aircraft cannot revert to firmware version 01.00.02.11 or earlier once the firmware is updated.
- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the Zenmuse Z30, XT S, XT2 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V1.9.0R or later.



M300 RTK Release Notes

| | |
|------------------------------|--|
| Released Date: | 2020.08.24 |
| Aircraft Firmware: | v01.00.02.11 |
| Remote Controller Firmware: | v01.00.02.13 |
| Pilot App Android | v1.9.0R |
| D-RTK 2 Mobile Station: | v03.00.00.13 |
| Intelligent Battery Station: | v01.05.06.06 |
| Intelligent Flight Battery: | v01.02.05.28 |
| Zenmuse H20 / H20T: | v01.00.02.11 |
| Zenmuse Z30: | v01.00.06.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.02.01.13 |
| DJI Assistant 2 For Matrice: | v2.0.13 |
| | Aircraft / Remote Controller: DJI Assistant 2 / App Zenmuse H20 / H20T: microSD card / DJI Assistant 2 / App D-RTK 2 Mobile Station: DJI Assistant 2 |
| Firmware Upgrade Method: | The built-in DJI Pilot app: will be updated with the Remote Controller firmware Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

Flight Mission

- Added Waypoint Monitor, where the next two waypoints can be displayed as blue diamonds on FPV and camera view. And the arriving waypoints height and flight route speed will be displayed on FPV view.
- The remote controller without flight control rights supports to display the execution status of the simplified route.
- Added Linear Flight Mission, supporting mapping scenes such as rivers and highways.
- The photos taken during Flight Mission are automatically stored in different folders, and the folder names can be customized.

AI Spot-Check

- Added oblique selection box to select the object in the photo for AI Spot-Check.
- The camera will be automatically set to zoom camera in AFS mode. Photo capturing and video recording are disabled to avoid disoperation for AI Spot-Check.
- Optimized the AI Spot-Check stability, improving operation efficiency and user experience.

Firmware Update

- Added a consistency firmware update entrance in the Health Management System.
- Optimized the firmware update in app efficiency.



M300 RTK Release Notes

- Adjusted the minimum battery power requirement for firmware update to 25% for the aircraft and 50% for the remote controller.

Flight Controller

- Added RTK single point backup to improve flight reliability in special scenarios.
- Optimized the return home algorithm during low battery mode to improve the safety of long-distance return home in windy weather.
- Optimized the Three Propeller Emergency Landing feature to improve the controllability during landing.
- The maximum descent speed of P mode is increased from 3 m/s to 4 m/s.

Smart Pin & Track

- Added Look At feature where user can control the gimbal and camera to focus to PIN point using one click.
- Added support to modify the GPS 3D coordinates of the PIN point on map page.
- Adjusted to display the height of RNG and Smart Track as altitude.
- Optimized the Smart Track algorithm to improve tracking accuracy and stability.
- Optimized the RNG feature to improve the stability of ranging.

DJI Pilot App

- Added the ability to display the GPS coordinates of the aircraft on the map page.
- Added tutorial videos academy.
- Added the function to manually switch to the attitude mode, and the T/P/S mode can be set to A/P/S mode in the app.
- Added functionality to export the remote control logs by flight to improve log export efficiency.
- Added an animated prompt for tightening the aircraft arm sleeves.
- Added cache cleaning for Pilot App (such as: pictures, App logs).
- Adjusted to set the top and bottom vision system separately.
- Adjusted the auxiliary light to auto mode after turned off Discreet Mode.
- Adjusted the high wind warning display from the absolute direction to the direction relative to the aircraft.
- Optimized the Enterprise Shield by adding auto activation and status checking.
- Added a vertical speed bar display to the FPV and camera view, improving the flight experience.
- Optimized the pre-flight check list by adding the status display of battery, RTK and other modules.

Advanced Dual Operator Mode

- Added functionality to control the zoom of the camera by using the joystick of the RC with gimbal control.
- Add a pop-up prompt to indicate that the features that remote controller B is not supported, improving the remote controller B operation experience.
- Optimized the display of the gimbal video transmission for the aircraft flight controller pilot. The remote controller without gimbal control can show the camera type and zoom rate.

Video Transmission System

- Added functionality to support the adaptive bit rate for the Video Transmission System of PSDK camera.
- Adjusted the power map to FCC in Hong Kong, China.



M300 RTK Release Notes

Sensing System

- Adjusted the horizontal obstacle avoidance status to four-way independent display, and supported to use the infrared sensor for obstacle avoidance once the vision system obstacle avoidance failed.
- Optimized the positioning stability for the vision system.

Remote Controller

- Added functionality to control the camera zoom by rotating the Gimbal Pan Control Dial with holding the Confirm Button.
- Added the remote controller vibration for reminding when the RTK/GPS/vision signal is lost.
- Added functionality to adapt external mobile devices (recommended devices: Samsung Galaxy Tab S6, Xiaomi tablet 4, Huawei M3, M5, M6).

Notes:

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the ZenmuseZ30, XT S, XT2 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V1.9.0R or later.



M300 RTK Release Notes

| | |
|------------------------------|---|
| Released Date: | 2020.06.04 |
| Aircraft Firmware: | v01.00.01.09 |
| Remote Controller Firmware: | v01.00.01.08 |
| Pilot App Android | v1.8.0R |
| D-RTK 2 Mobile Station: | v03.00.00.13 |
| Intelligent Battery Station: | v01.05.06.04 |
| Intelligent Flight Battery: | v01.02.05.22 |
| Zenmuse H20 / H20T: | v01.00.01.08 |
| Zenmuse Z30: | v01.00.06.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 |
| DJI X-Port: | v01.01.01.00 |
| DJI Assistant 2 For Matrice: | v2.0.11 |
| Firmware Upgrade Method: | Aircraft / Remote Controller / D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Gimbal and Camera: microSD card Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

Aircraft Firmware

- Fixed the issue where the RTK positioning data is difficult to converge or the convergence time is too long in some areas.

Notes:

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the ZenmuseZ30, XT S, XT2 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V1.8.0R or later.



M300 RTK Release Notes

| | |
|------------------------------|---|
| Released Date: | 2020.05.14 |
| Aircraft Firmware: | v01.00.01.08 |
| Remote Controller Firmware: | v01.00.01.08 |
| Pilot App Android | v1.8.0R |
| D-RTK 2 Mobile Station: | v03.00.00.13 |
| Intelligent Battery Station: | v01.05.06.04 |
| Intelligent Flight Battery: | v01.02.05.22 |
| Zenmuse H20 / H20T: | v01.00.01.08 |
| Zenmuse Z30: | v01.00.06.10 |
| Zenmuse XT2: | v01.00.03.50 |
| Zenmuse XT S: | v01.00.00.09 (Coming soon) |
| DJI X-Port: | v01.01.01.00 |
| DJI Assistant 2 For Matrice: | v2.0.11 |
| Firmware Upgrade Method: | Aircraft / Remote Controller / D-RTK 2 Mobile Station: DJI Assistant 2 The built-in DJI Pilot app: will be updated with the Remote Controller firmware Gimbal and Camera: microSD card Intelligent Battery Station: App (Connect the Battery Station to the remote controller and update it on the HMS page in the DJI Pilot app.) |

What's new

- Adds support for Zenmuse XT S, Z30 and XT2. Note that XT2 can only be mounted on the 1st gimbal port.
- Supports the ability to select two video transmissions (FPV included) to display. Supports up to three video transmissions when using Advanced Dual Operator Mode.
- Updates the manuals in DJI Pilot app.
- Supports customizable button setting for the remote controller.
- Supports Update All function to update firmware (aircraft, remote controller and H20 / H20T) in app.
- Adds Primary Flight Display (PFD) in app, which can help users to see the aircraft information and 6 Directional Sensing and Positioning information more intuitively and easily.
- Adds Smart Pin & Track, allowing users to locate and track the mobile target, and share the location.
- Supports photo download from the camera for OSDK.
- Supports accurate meta-tagging for PSDK payloads.
- Adds support for Three-propeller Emergency Landing if the aircraft loses the capability of one motor



M300 RTK Release Notes

during flight.

- Adds support for GEO Unlocking.
- Optimizes obstacle avoidance logic in the vertical direction of the aircraft.
- Optimizes control precision for AI Spot-check.
- Optimizes battery self-heating and protection strategy and battery balancing function.
- Fixed occasional issue: Breakpoints prevent the aircraft from continued flight in Flight Mission.

Notes:

- Make sure that the aircraft, remote controller, battery, D-RTK 2 mobile station (if used), payload (if used) are updated to the latest firmware version.
- Download the latest firmware from official website to microSD card to update the ZenmuseZ30, XT S, XT2 or H20 / H20T.
- It is required to use the DJI Pilot app built-in the remote controller, or download the app of V1.8.0R or later.